

SPECIFICATION

Model: R70

Hardware		Communications & Networking	
CPU	ARM Cortex A73 Octa-core (2.0GHz)	Phone Call	GSM /WCDMA/CDMA 1X/VoLTE
GPU	Arm Mali--G72 MP3	2G	GSM/CDMA 1X/EDGE/GPRS/WAP
RAM	8G	2G Band	GSM (B2/3/5/8)
Internal Memory	128G	3G	WCDMA 3.75G (HSDPA+ 42.2Mbps, HSUPA+
External Memory	Micro SD card (T-FLASH card), max 256GB	3G Band	WCDMA (B1/2/5/8) ,Evdo: BC0/BC1 CDMA:
Main Camera	13.0MP(AF) with flash led	4G	FDD: 150Mbps down, 50Mbps UP TDD: 150M
Sub Camera	5.0MP	4G Band	TD-LTE (B38/39/40/41); FDD LTE (B1/2/3/4/5,
Battery	10000mAh	WI-FI	Dual-band WIFI (2.4GHz/5Ghz) single stream &
Display	7 inch IPS/AFFS 1280*720 HD industrial 1000nit Sunlight Readable	Bluetooth	5.0 Low Energy (LE)
Touch Panel	Capacitive/frosted tempered film supports glove touch/spray/active capacitive pen	Industrial & Reliability Design	
IO/Sensor/Navigation		Shake-proof	1-19Hz/1.0mm; 19-200Hz/1.0g
SIM Card	1.8/3.3V SIM card	Dropproof /IK	MIL-STD-810G/Method516.6/Procedure IV &
TF Card	Micro SD card (T-FLASH card); max 256GB	Waterproof	Class 5 (IEC 60529)
Headphone	3.5mm (CTIA)	Dustproof	Class 6 (IEC 60529)
Charging interface	Type-C & 2pin pogo pin & DC 5V (direct battery charging)	Operating temperature	-20°C to 55°C
Data interface	USB Type-A(Host)*1, Type-C*1	Storage Temperature	-40°C to 80°C
Gravity sensor	Support	Reliability	MTBF>5000h; MTTR<0.5h
Direction Sensor	Support	RH	5%RH-95%
Magnetic Field Sensor	Support	Operating Altitude	Max: 4,500 m (15,000 feet)
Gyro sensor	Support	Certification/OS/Software	
Rotation Vector	Support	Certification	3C /FCC/CE/ROHS/IP65 (IEC 60529)
Light-sensor	Support	Language	English, Spanish, Portuguese (Brazil), Portuguese French, Polish, Romanian, Turkish, Russian, Ar Hindi, Hebrew, Simplified, Chinese, Chinese Tr
Acceleration sensor	Support		
Motion sensor	Support	OS	Android 10/11/13 (Continuous Updates)
Charger	5.0V 2A-10W	Package/Warranty terms	
Navigation	GPS+Beidou+Glonass+AGPS+SBAS (EPO 2.5m)	Warranty	24 months
Appearance		Package	USB cable/Charger 5V 2A /Introduction manual
Size	237*137*29mm (LxWxH)		
Weight	780g		

Color & Material

Gray (ABS+PC) + Black (TPU)

Package

USB Cable/Charger 3V 2A/Introduction Manual



11.5Mbps), EVDO

: BC0/BC1

bps downlink, 50Mbps uplink

(7/8/12/17/20/28)

302.11 a/b/g/n/ac



Touch Panel IK05



ese (Portugal), Italian, German, Dutch,
abic, Indonesian, Malay, Thai, Vietnamese,
raditional, etc.



il/Screen protector/Packing box

11/screen protector/packing box